


## Click Torque Wrench



## Flexible Ratchet Head

- \*All-steel construction,ratchet head flexes up to 15 degrees in either direction.
- \*45-tooth reversible ratchet head for both clockwise and counterclockwise\*\* operation.
- \*+/-4% accuracy in clockwise direction exceeds international specifications.
- \*Unique, stay-in-place,Lock Ring makes adjustments easier and secures selected torque from accidental change.
- \*Metric scale with fine increments and reference English scales are easy to read and set.
- \*The identity code marked on each wrench makes it possible to keep accurate records.
- \*Non slip grooved handle.

<sup>\*\*</sup>If calibrated for counterclockwise operation





Part Code	Drive	Torque Range		Length	Width	Weight
		N.m	Lb.ft	mm	mm	kg
GM120F	1/4	4.0-20	30-180*	319	35	0.68
GM2125F	3/8"	25-125	20-90	468	38	1.04
GM3125F	1/2"	25-125	20-90	468	38	1.04
GM3335F	1/2"	65-335	50-250	562	40	1.30
GM4335F	3/4"	65-335	50-250	562	40	1.34

\*Unit is Lb.in

Part Code	Drive	Torque Range		Length	Width	Weight
		Lb.ft	N.m	mm	mm	kg
G1200F	1/4"	40-200*	4.0-22	310	35	0.68
G275F	3/8"	15-75	20-100	450	38	1.04
G375F	1/2"	15-75	20-100	450	38	1.04
G2100F	3/8"	20-100	25-135	450	38	1.04
G3100F	1/2"	20-100	25-135	450	38	1.04
G3250F	1/2"	50-250	70-340	560	40	1.30
G4250F	3/4"	50-250	70-340	560	40	1.34

\*Unit is Lb.in