



## Cyclone Magnum Pneumatic Torque Wrench

### Ergonomic Features

#### Direction Control

Loosen



Tighten



#### Lift Handle




### Optional Digital Read Out Item# AT-DR



- Display Torque Output  
Nm & ft-lbs



- Display Air Pressure  
Bar & Psi



- USB Interface



### Removable Drives



| Hex Size | AT400     | AT800      | AT1800      | AT3000      |
|----------|-----------|------------|-------------|-------------|
| 5/8"     | AT400-HX1 | AT800-HX1  |             |             |
| 3/4"     | AT400-HX2 | AT800-HX2  | AT1800-HX2  | AT3000-HX2  |
| 7/8"     |           |            | AT1800-HX3  | AT3000-HX3  |
| 1"       |           | AT1800-HX4 | AT3000-HX4  |             |
| 1-1/4"   |           |            |             | AT3000-HX5  |
| 14mm     | AT400-HX7 | AT800-HX7  |             |             |
| 17mm     | AT400-HX8 | AT800-HX8  |             |             |
| 19mm     | AT400-HX9 | AT800-HX9  | AT1800-HX9  | AT3000-HX9  |
| 22mm     |           |            | AT1800-HX10 | AT3000-HX10 |

\* Note: Use of hex drives may require special reaction bars

| Model  | Dimension A1<br>Inches<br>[mm] | Dimension A<br>Inches<br>[mm] | Diameter<br>Inches<br>[mm] | Weight<br>lbs.<br>[Kg] | Torque Range<br>Ft-lbs<br>[Nm] | Dimension B<br>Inches<br>[mm] | Square<br>Drive<br>Size |
|--------|--------------------------------|-------------------------------|----------------------------|------------------------|--------------------------------|-------------------------------|-------------------------|
| AT400  | 9.85<br>[250.27]               | 9.7<br>[247.24]               | 2.25<br>[57.15]            | 11.5<br>[5.2]          | 44-400<br>[60-540]             | 5.4<br>[136.32]               | 3/4"                    |
| AT800  | 9.85<br>[250.11]               | 9.7<br>[247.09]               | 2.97<br>[75.34]            | 14<br>[6.4]            | 88-800<br>[120-1100]           | 5.1<br>[129.84]               | 3/4"                    |
| AT1800 | 12.12<br>[307.85]              | 11.7<br>[297.51]              | 3.42<br>[86.87]            | 21<br>[9.5]            | 200-1800<br>[275-2450]         | 7.5<br>[191.27]               | 1"                      |
| AT3000 | 13.00<br>[329.95]              | 12.8<br>[326.92]              | 3.80<br>[96.52]            | 27.5<br>[12.5]         | 333-3000<br>[450-4070]         | 8.6<br>[220.24]               | 1"                      |

Elevate your standards . . . Set a new expectation.  
Use the **CYCLONE MAGNUM**

- 1 length with Digital Torque Readout
- 2 Length without Digital Torque Readout
- 3 Ring Gear Diameter
- 4 Weight of complete tool with reaction bar



|  | Item          | Item          | Item           | Item           |
|--|---------------|---------------|----------------|----------------|
| Complete System without digital Readout* | AT400CMLPT    | AT800CMLPT    | AT1800CMLPT    | AT3000CMLPT    |
| Complete System with digital Readout*    | AT400DR-CMLPT | AT800DR-CMLPT | AT1800DR-CMLPT | AT3000DR-CMLPT |
| Cage Only                                | MAG-AIRCAGE   | MAG-AIRCAGE   | MAG-AIRCAGE    | MAG-AIRCAGE    |
| Tool without digital readout             | AT400         | AT800         | AT1800         | AT3000         |
| Tool with digital readout                | AT400DR       | AT800DR       | AT1800DR       | AT3000DR       |

\* Includes Tool and Cage